



8-145.000

	D			D	S	B*		
	t , 0							
	200	300	425					
8-145.000	57	-	-	219	6	460	9,70	1 100 .
8-145.000-01	76	57	-	273	6	515	14,00	1 450 .
8-145.000-02	89; 108	76; 89	57	325	6	565	16,50	1 740 .
8-145.000-03	133	108	76; 89	377	9	615	26,70	2 590 .
8-145.000-04	159	133; 159	108	426	7	665	24,00	2 570 .
8-145.000-05	219	-	133; 159	478	7	720	26,70	2 600 .
8-145.000-06	273	219	-	530	8	770	34,10	3 240 .
8-145.000-07	325; 377	273; 325	219; 273	630	8	920	40,00	3 800 .
8-145.000-08	426	377	325	720	8	960	45,20	4 290 .
8-145.000-09	478; 530	426; 478	377; 426	820	8	1060	51,20	4 840 .
8-145.000-10	630	530	-	920	9	1160	64,00	5 750 .
8-145.000-11	720	630	-	1020	10	1260	77,90	7 100 .
8-145.000-12	820; 920	720; 820	-	1220	11	1460	103,80	8 800 .
8-145.000-13	1020	920; 1020	-	1420	14	1660	150,50	12 700 .
8-145.000-14	1220	1220	-	1620	14	1860	174,00	14 790 .
8-145.000-15	1420	1420	-	1760	14	2000	188,00	15 970 .

* -